
DALLMER

floor drain DallDrain Pure Plan, DN 40, 100 x 100 mm

Part number: 517074 GTIN: 4001636517074 Rebate group: 6





Description:

floor drain DallDrain Pure Plan, DN 40, 100 x 100 mm Floor drain including grating DallDrain Pure with stainless steel grate in plastic frame. Side outlet DN 40, with ball joint, adjustable from 0 - 15 degrees.

Specification

- Stainless steel grate, plastic frame
- Integrated screed anchoring
- Flexible, click-in sealing sleeve for secure connection to bonded and
- sheet waterproofing conforming to DIN 18534
- Fully removable, two-piece trap insert and rodding eye, 22 mm water seal
- (deviating to DIN EN 1253)
- Temporary blanking plate
- Three sound-insulated mounting feet for fixing and height adjustment 55-250 mm
- Spigot can be shortened for floorings 10 36 mm (including adhesive)
- Screed reinforcement element for protection of the outlet

Material

Drain body and outlet polypropylene, highly impact-resistant; 1.4301 stainless steel grate, load class K 3 (300 kg); spigot and frame in ABS Pre-assembled set consisting of parts no. 517258 + 517227 + 517340.

Grating with positioning aid laterally adjustable +/- 2.5 mm. Can be used with sound insulation mat DallDrain (part no. 517326) and

mounting aid DallDrain Plan (part no. 517302).

Flow rates tested to DIN EN 1253:

Nominal	Product stan-	Min. flow rate according to	Water level according to	Flow rate at water level	Flow rate at water level
diameter	dard	norm	norm	10 mm	20 mm
DN 40	DIN EN 1253	0.40 l/s	20.00 mm	0.47 l/s	0.54 l/s

<u>Spare parts:</u>

501011	grate E 90, 90 x 90 mm		trap insert DallDrain Plan
517258	grating DallDrain Pure, 100 x 100 mm	517197	sealing sleeve DallDrain
517340	mounting feet DallDrain		

Dallmer GmbH + Co KG · Wiebelsheidestraße 25 · 59757 Arnsberg · Tel.: +49 2932 9616-0 · Fax: +49 2932 9616-222 www.dallmer.com · info@dallmer.de Subject to modifications due to technical development, errors and misprints