



floor drain DallDrain Pure vertical OM, DN 50/DN 100, 100 x 100 mm

Part number: 517685
 GTIN: 4001636517685
 Rebate group: 6



Description:

floor drain DallDrain Pure vertical OM, DN 50/DN 100, 100 x 100 mm
 conforming to DIN EN 1253

Floor drain including grating DallDrain Pure with stainless steel grate in ABS frame.
 Outlet DN 50/DN 100 vertical.

Specification

- Stainless steel grate, plastic frame
- Integrated screed anchoring
- Flexible, click-in sealing sleeve for secure connection to bonded and sheet waterproofing conforming to DIN 18534
- Fully removable, two-piece trap insert and rodding eye, 50 mm water seal (conforming to DIN EN 1253)
- Temporary blanking plate
- Spigot can be shortened for floorings 10 – 36 mm (including adhesive)

MATERIAL

Polypropylene drain body and outlet, highly impact-resistant;
 1.4301 stainless steel grate, load class K 3 (300 kg); spigot and frame in ABS
 Pre-assembled set consisting of parts no. 517258 + 517234.

Grating with positioning aid laterally adjustable +/- 2.5 mm.

Fire and sound-insulating collar - installation kit 2 (Part No. 515025) or

fire protection kit 12 (Part No. 515438) applicable.

Flow rates tested to DIN EN 1253:

Nominal diameter	Product standard	Min. flow rate according to norm	Water level according to norm	Flow rate at water level 10 mm	Flow rate at water level 20 mm
DN 50	DIN EN 1253	0.80 l/s	20.00 mm	0.72 l/s	1.30 l/s